

WONDER POLE® - HIGH POLE INSTRUCTIONS

***** Please Read *****

item# highpole-621pro-strikerrod

Thank you for purchasing the High Pole Kit from Wonder Pole®. Extend the pole to the desired height by opening the “Sure Lock” grip (use a counter clockwise turn of the top portion of the grip to open). Close the Sure Lock grip (use a clockwise rotation) to keep the pole section extended. Caution: Do not over-tighten the Sure Lock grips. Use the security clamps provided to ensure there is no slippage during transit. We recommend extending the three bottom sections of the high pole first to about 12’ or 15’, and then extending the pole the rest of the way using the remaining sections to give the high pole additional rigidity.

This kit includes (1) Striker Rod Adapter (*item# highpole-striker-34*) and (2) Striker Rods. The Striker Rod Adapter has two holes at each end. The end with the larger hole slips over and onto the top mast (3/4” section) of your High Pole. The 3/4” top mast of the high pole only needs to be extended 6” to 12” if desired. Using the hex wrench supplied, secure the Striker Rod Adapter to your high pole being careful not to over tighten the set screws, and damage the pole.

Insert the Striker Rod into the small hole at the top of the Striker Rod Adapter, as illustrated in the photograph. Be sure to insert at least 8” of the Striker Rod into the Striker Rod Adapter. Tighten the two top hex screws to secure the Striker Rod. Typically, you will adjust the height of your striker rod to around 6” above the load height.



When placing the high pole into the holder on your vehicle be sure that the fiberglass High Pole is not damaged by coming into contact with metal or other materials used to fabricate the mount, tubes, or other accessories. You should place a buffer material between the metal and the high pole to prevent damage or wear.

Install the protective rubber “Shock Pad” provided onto the bottom pole section to sit between the bottom of the pole and your pole mount. This provides protection when contacting the metal at the

base of your pole mount.

This kit includes (1) Security Clamp Set (*item# highpole-clampset-34*) The security stainless steel clamps provided should be used to prevent slippage of the sections during transport or vehicle operation.

If you have any questions or concerns, please contact us at 1-503-585-1179. Thank you!



FF Manufacturing, Inc.
Headquarters: Salem, Oregon USA
Phone: 1-503-585-1179
Email: support@ffmanufacturing.com
WWW.WONDERPOLE.COM